

# Quote Request

Fill out form and give to your local representative or send to [sales@oilsafe.com](mailto:sales@oilsafe.com)



Customer Name and Contact Information \_\_\_\_\_

Enter your preferred model part number or choose a system type for custom configuration.

Model Part # \_\_\_\_\_ or  Advanced System  Lubrication Work Center

## How many lubricants do you need to store?

This will determine the number of tanks that you need \_\_\_\_\_

## Complete the following table and questions

SYSTEM REQUIREMENTS ( Required for all Systems )				CUSTOMIZATION ( Lubrication Work Center Only )
Tanks	Size (Gallons) (30, 65, 120 or 240)	Viscosity	Type of Fluid	Hose Reel (25')
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				

Max viscosity for all systems is ISO 680.

## Systems include:

**Enhanced Fire Protection and Fire Safety (standard)** – All systems come standard with MSHA accepted 811HT rated hosing and include auto-shut off tank isolation valves.

**Custom ID - Labeling Package (standard)** – All systems come standard with ID Labeling to identify your lubricants.

**Electric motors come with 110V or 240v single phase or pneumatic (standard)** – If alternate required confirm:

Country the System will be used in \_\_\_\_\_

## Accessories

Voltage \_\_\_\_\_ Hertz \_\_\_\_\_

- Storage Cabinet     
  Suction Hose Cart     
  Suction Hose Wall Mounted Rack     
  Overfill Alarm Audible & Flashing Light